

Energía Solar COMPONENTES - Inversores Off Grid



Salida De Onda		Onda Pura				
Modelo		NV-P300	NV-P600	NV-P1000	NV-P2000	NV-P3000
Salida	Salida de Voltaje (W)	300	600	1000	2000	3000
	Energía Pico	600	1200	2000	4000	6000
	Frecuencia	60Hz				
Entrada	Carga de No Corriente	<0.5A, <0.3A	<0.7A, <0.4A	<0.9A, <0.4A	<3.2A, <1.4A	<3.5A, <2.1A
	Voltaje de Trabajo DC	12V / 24V	12V / 24V	12V / 24V	12V / 24V	12V / 24V / 48V
	Rango del Voltaje	10-15V 20-30V	10-15V 20-30V	10-15V 20-30V	10-15V 20-30V	10-15V, 20-30V, 40-60V
	Alarma de Bajo Voltaje	11V, 21V	11V, 21V	11V, 21V	11V, 21V	11V, 21, 42V
	Protección de Voltaje	10V, 20V	10V, 20V	10V, 20V	10V, 20V	10V, 30V, 40V
	Protección Sobre-Voltaje	15V, 30V	15V, 30V	15V, 30V	15V, 30V	15V, 30V, 60V
	Eficiencia Máxima	94%				
Dimensiones Del Producto (mm)		172x150x58	262x150x76	367x150x76	454x180x142	529x180x142
Peso (gr)		940	1710	2730	3750	6020